

# Submittal Spec Sheet Eaton® Innovative Technology® ITC-ISDN Models Surge Protective Devices

### Introduction

Since 1980, Eaton's Innovative Technology has provided Surge Protective Devices (SPDs) to power quality equipment users around the world. Whatever your electrical surge protection need may be, Eaton's Innovative Technology has a Surge Protective Device to fill it!

# **General Features**

- Description Telecommunication line transient voltage surge suppression devices
- Application Standard 3002/C2 unconditioned voice grade lines, fax, modem and ISDN lines
- Warranty 5-Year Free Replacement
- Manufacturer Qualifications ISO® 9001:1994 Quality System Certification BSI FM 30833

# **Mechanical and Electrical Features**

- Enclosure ABS Plastic UL® 94V-0 with integral multi-point mounting feet
- Connection -
  - Lines (ITC-4T, -6T, -12T): wire clamping box terminal strips, #14 (2.5 mm2) wire max.
  - Lines (ITC-RJ14): 1-pair or 2-pair RJ11 or RJ14 modular connectors
  - Ground: 10/32 lug with wire clamping box terminal #6 – 12 AWG (16 – 4 mm²)
- Weight
  - RJ14 ≈ 0.5 lb (0.22 kg)
  - -4T, 6T 12T  $\approx$ 1 lb (0.45 kg)
- Protection Modes All Modes. Normal mode: tip-ring, common mode: tip-ground and ring-ground
- Data Rate Up to 200 kbps
- Response Time ≤1 nanosecond
- EMI/RFI Attenuation —Up to 46 dB normal mode, up to 51 dB common mode
- Maximum Continuous Operating Voltage 130 Vrms (183 Vpk) tip-ring, tip-ground and ring-ground
- Peak Surge Current 30 kA per pair, 10 kA per mode
- Maximum Current
  - RJ14: 1 Amp @ 25°C
  - 4T/6T/12T: 2.5 Amp

### **Performance Data**

	IEC 10 x 700 μS Impulse
Mode	Measured Limiting Voltage*
Tip-G or L-G	300
Ring-G or L-G	300
Tip-Ring or L-L	300

<sup>\*</sup> Test environment: static, positive polarity. All voltages are peak (±10%), time base = 1 ms.

- 3.13 (79.6) → 2.13 (54.1) 4.25 (108.0) Ø 3.75 (95.3) 5.18 (131.8) 0.19(5)4.78 Dia. (121.9)3.33 (84.6)2.03 1.80 (51.6)(45.8)ITC-RJ14-ISDN ITC-12T-ISDN Dimensions are in 3.13 (79.6) Inches (mm) 2.13 (54.1) 0 3.49 (89.0) 3.25 (82.8) 5.18 (131.8) 4.78 2.47 (62.6) <u></u> (121.9) 2.00 (51.0)苗. 2.15 1.80 (54.8)(45.8)ITC-6T-ISDN ITC-4T-ISDN

Innovative Technology is a registered service mark of Eaton Corporation. UL is a federally registered trademarks of Underwriters Laboratories Inc. ISO is the registered trademark and sole property of the International Organization for Standardization

Eaton Corporation Innovative Technology TVSS Products 1000 Cherrington Parkway Moon Township, PA 15108-4312 IISA

Phone: 1-800-525-2000 Web: www.itvss.com



